

□NF 型 無熔線斷路器—配電、配線用

型 名	額定電流(A)	啓斷容量 KA 非對稱值/對稱值				牌 價	備 註
		220V	380V	440V	600V		
NF 30-SB 2P	5.10.15.20.30	5	2.5	2.5	1.5	555	
NF 30-SB 3P	5.10.15.20.30	5	2.5	2.5	1.5	745	
NF 50-CB 2P	10.15.20.30.40.50	5	2.5	2.5	1.5	710	
NF 50-CB 3P	10.15.20.30.40.50	5	2.5	2.5	1.5	885	
NF 50-SB 2P	10.15.20.30.40.50	10	7.5	7.5	5	905	
NF 50-SB 3P	10.15.20.30.40.50	10	7.5	7.5	5	1,010	
NF 50-HS 2P	10.15.20.30.40.50	30/25	18/15	10	5	935	
NF 50-HS 3P	10.15.20.30.40.50	30/25	18/15	10	5	1,045	
NF 60-HS 2P	60	30/25	18/15	10	5	1,205	
NF 60-HS 3P	60	30/25	18/15	10	5	1,385	
NF 100-CB 2P	60.75.100	10	7.5	7.5	5	1,255	
NF 100-CB 3P	60.75.100	10	7.5	7.5	5	1,580	
NF 100-MB 2P	10.15.20.30.40.50	18/15	10	7.5	5	990	
NF 100-MB 2P	60.75.100	18/15	10	7.5	5	1,280	
NF 100-MB 3P	10.15.20.30.40.50	18/15	10	7.5	5	1,025	
NF 100-MB 3P	60.75.100	18/15	10	7.5	5	1,495	
NF 100-SB 2P	10.15.20.30.40.50.60.75.100	30/25	20/18	12/10	10/7.5	1,245	
NF 100-SB 3P	10.15.20.30.40.50.60.75.100	30/25	20/18	12/10	10/7.5	1,600	
NF 100-HB 2P	15.20.30.40.50.60.75.100	60/50	35/30	25/22	18/15	1,865	
NF 100-HB 3P	15.20.30.40.50.60.75.100	60/50	35/30	25/22	18/15	2,220	
NF 100-H 2P	15.20.30.40.50.60.75.100	100/85	60/50	50/42	30/25	2,895	
NF 100-H 3P	15.20.30.40.50.60.75.100	100/85	60/50	50/42	30/25	3,205	
NF 100-CBS 2P	10.15.20.30.40.50	10	7.5	7.5	5	840	
NF 100-CBS 2P	60.75.100	10	7.5	7.5	5	1,145	
NF 100-CBS 3P	10.15.20.30.40.50	10	7.5	7.5	5	935	
NF 100-CBS 3P	60.75.100	10	7.5	7.5	5	1,340	
NF 100-SBS 2P	10.15.20.30.40.50	30/25	20/18	12/10	10/7.5	940	
NF 100-SBS 2P	60.75.100	30/25	20/18	12/10	10/7.5	1,150	
NF 100-SBS 3P	10.15.20.30.40.50	30/25	20/18	12/10	10/7.5	1,055	
NF 100-SBS 3P	60.75.100	30/25	20/18	12/10	10/7.5	1,465	
NF 125-SB 2P	125	30/25	20/18	12/10	10/7.5	1,255	
NF 125-SB 3P	125	30/25	20/18	12/10	10/7.5	1,670	
NF 125-HB 2P	125	60/50	35/30	30/25	16/15	1,875	
NF 125-HB 3P	125	60/50	35/30	30/25	16/15	2,380	
NF225-CB 2P	125.150.175.200.225	30/25	20/18	12/10	10/7.5	2,570	
NF225-CB 3P	125.150.175.200.225	30/25	20/18	12/10	10/7.5	3,290	
NF225-SB 2P	125.150.175.200.225	60/50	35/30	30/25	18/15	3,800	
NF225-SB 3P	125.150.175.200.225	60/50	35/30	30/25	18/15	4,415	

□NF 型 無熔線斷路器－配電、配線用

型 名	額定電流(A)	啓斷容量 KA 非對稱值/對稱值				牌 價	備註
		220V	380V	440V	600V		
NF225-HB 2P	125.150.175.200.225	100/85	60/50	50/42	30/25	4,140	
NF225-HB 3P	125.150.175.200.225	100/85	60/50	50/42	30/25	4,550	
NF250-CB 2P	250	35/30	25/22	25/22	15/14	3,135	
NF250-CB 3P	250	35/30	25/22	25/22	15/14	3,515	
NF250-SB 2P	250	60/50	35/30	30/25	18/15	4,635	
NF250-SB 3P	250	60/50	35/30	30/25	18/15	4,985	
NF400-CA 2P	250.300.350.400	35/30	25/22	25/22	15/14	5,390	
NF400-CA 3P	250.300.350.400	35/30	25/22	25/22	15/14	5,930	
NF400-CTA2P	250.300.350.400	60/50	35/30	30/25	22/20	6,620	
NF400-CTA3P	250.300.350.400	60/50	35/30	30/25	22/20	7,430	
NF400-CTAT2P	250.300.350.400	60/50	40/35	35/30	—	6,955	
NF400-CTAT3P	250.300.350.400	60/50	40/35	35/30	—	7,795	
NF400-S 2P	250.300.350.400	100/85	50/42	50/42	30/25	8,055	
NF400-S 3P	250.300.350.400	100/85	50/42	50/42	30/25	8,385	
NF400-HS 2P	250.300.350.400	100/85	60/50	50/42	30/25	7,345	
NF400-HS 3P	250.300.350.400	100/85	60/50	50/42	30/25	7,760	
NF600-CA 3P	500.600	35/30	25/22	25/22	15/14	11,620	
NF600-CTA 3P	500.600	60/50	35/30	30/25	22/20	11,970	
NF600-CTAT3P	500.600	60/50	40/35	35/30	—	12,985	
NF600-S 3P	500.600	100/85	60/50	50/42	30/25	12,985	
NF800-SB 3P	700.800	60/50	35/30	30/25	22/20	18,415	
NF800-H 3P	700.800	100/85	60/50	60/50	35/25	18,890	
NF800-E 3P	400.450.500.600.700.800	100/85	60/50	60/50	35/25	23,865	
NF800-HS 3P	700.800	150/130	120/100	100/85	75/65	26,710	
NF1000-HS3P	1000	150/130	120/100	100/85	75/65	38,900	
NF1000-E 3P	500.600.700.800.900.1000	150/125	100/85	100/85	60/50	41,640	
NF1200-HS3P	1200	150/130	120/100	100/85	75/65	47,480	
NF1200-E 3P	600.700.800.1000.1200	150/125	100/85	100/85	60/50	48,750	
NF1600-HS3P	1400.1600	150/130	120/100	100/85	75/65	53,420	

□NF 型 高啓斷容量—配電、配線用

型 名	額定電流(A)	啓斷容量 KA 非對稱值/對稱值				牌 價	備註
		220V	380V	440V	600V		
NF100-HC 2P	15.20.30.40.50.60.75.100	120/100	75/65	60/50	—	3,135	
NF100-HC 3P	15.20.30.40.50.60.75.100	120/100	75/65	60/50	—	3,440	
NF225-HC 2P	125.150.175.200.225	120/100	75/65	60/50	—	4,350	
NF225-HC 3P	125.150.175.200.225	120/100	75/65	60/50	—	4,875	
NF400-HC 2P	250.300.350.400	120/100	75/65	60/50	—	8,455	
NF400-HC 3P	250.300.350.400	120/100	75/65	60/50	—	10,590	
NF600-HC	500.600	120/100	75/65	60/50	—	15,860	
NF800-HC	700.800	120/100	75/65	60/50	—	20,050	

□NF無熔線斷路器附屬裝置

品名	規格	適用極數	適用斷路器機種	牌價
外部操作把手	EH50	3P	NF 30-SB NF 50-CB,SB,HS NF 60-HS NF 100-CBS,SBS,MB	546
	EH100	3P	NF 100-CB,SB,HB NF 125-SB,HB	648
	EH100H	2P,3P	NF 100H	648
	EH225	2P,3P	NF 225CB,SB NF 250CB,SB	779
	EH225H	2P,3P	NF 225HB	779
端子隔離蓋	TC50	2P	NF 30-SB NF 50-CB,SB,HS NF 60-HS NF 100-CBS,SBS,MB	142
		3P		
	TC100	2P	NF 100-CB,SB,HB NF 125-SB,HB	142
		3P		
	TC225	2P,3P	NF 100-H NF 225-CB,SB,HB NF 250-CB,SB	142
	TC400	2P,3P	NF 400-CA,CTA,CTAT,HS	688
TC600	3P	NF 400-S NF 600-CA,CTA,CTAT,S NF 800-SB,H,E	951	