

# 台芝無熔線斷路器

## 台芝無熔線斷路器

類別	型式	啓斷容量 KA 非對稱值/對稱值				DC		電 流 容 量		極數 P	定 價		
		220V 240V	380V	440V 480V	550V	125V	250V	AF	AT				
配 線 用 經 濟 型 【 E 】	EN100	16/15	10	7.5	5	5	5 (註 1)	100	5,10,15,20,30,40,50,60	2	880		
										3	950		
									75,100	2	1,050		
	EP100	30/25	20/18	10	7.5	7.5	7.5	100	60,75,100	2	1,300		
										3	1,600		
	EC225	25/22	20/18	20/18	15/14	15	10	225	125,150,175,200,225	2	2,300		
										3	2,900		
	EP225	30/25	20/18	20/18	15/14	15	10	225	125,150,175,200,225	2	2,400		
										3	3,100		
	EM400B	30/25	20/18	20/18	15/14	15	10	400	250	2	3,000		
										3	3,400		
	EN400	40/35	30/25	25/22	16/15	20	20	400	250,300,350,400	2	5,100		
3										5,600			
EP400	60/50	35/30	30/25	20/18	30	25	400	250,300,350,400	2	6,000			
				3					6,800				
EP600	60/50	35/30	30/25	22/20	30	25	600	500,600	3	11,000			
									3	18,000			
EP800	60/50	35/30	30/25	22/20	30	25	800	700,800	3	18,000			
									3	18,000			
配 線 用 標 準 型 【 S 】	SN100	30/25	20/18	10	7.5	7.5	5 (註 1)	100	5,10,15,20,30,40,50,60	2	900		
										3	1,000		
										4	1,700		
									75,100	2	1,100		
										3	1,400		
	SP100	60/50	35/30	30/25	16/15	20	15	100	15,20,30,40,50,60,75,100	2	1,700		
										3	2,100		
	SP225	60/50	35/30	30/25	20/18	30	25	225	125,150,175,200,225	2	3,500		
										3	4,100		
	SM400B	60/50	35/30	30/25	20/18	30	25	400	250	2	4,000		
										3	4,400		
	SG100	100/85	60/50	50/43	-	40	40	100	15,20,30,40,50,60,75,100	3	3,000		
SG225											225	125,150,175,200,225	4,300
SG400											400	250,300,350,400	7,600
SG600											600	500,600	12,600
SG1200	150/125	100/85	75/65	50/42	50	40 (註 2)	1200	700,800	3	23,000			
								1000		35,000			
								1200		43,000			
ESH1600	160/130	120/100	100/85	75/65	-	-	1600	可調整 800-1600	3	95,000			
										ESH2000	2000	可調整 1000-2000	140,000
						(註 3)							

(註 1)EN100&SN100 係完全電磁式，DC(直流)用須訂貨生產。

(註 2)台芝 SG1200 機種近期推出。

(註 3)ESH1600、ESH2000 係日本東芝原裝進口品。

# 台芝無熔線斷路器・漏電斷路器

## 台芝無熔線斷路器

類別	型式	啓斷容量 KA 非對稱值/對稱值			電 流 容 量			極數 P	定 價
		110/220V	220V	380V	AF	AT			
照明分電盤用 規格型【R】	R50	5	-		50	15,20,30,40,50		1	86
								2	200
	R100	-	5	-	100	60,75,100		3	420
								2	400
	HR100	10	-		100	15,20,30,40,50		1	120
								2	270
		-	10			60,75,100		3	580
								2	560
	PR100	15 (110V)	10	-	100	15,20,30,40,50		3	1,100
								2	205
		-	15	10		60,75,100		2	420
								3	960
				60,75,100		2	850		
						3	1,400		
照明分電盤用 插入型【L】	L50	5	-		50	15,20,30,40,50		1	86
								2	200
	L100	-	5	-	100	60,75,100		3	420
								2	400
	HL100	10	-		100	15,20,30,40,50		3	850
									1
		-	10			60,75,100		2	270
								3	580
	PL100	15 (110V)	10	-	100	15,20,30,40,50		2	560
								3	1,100
		-	15	10		60		1	205
								2	420
				60		3	960		
						2	850		
				3	1,400				

## 台芝漏電斷路器(漏電保護專用型)

類別	型式	短時間啓斷電流 KA		電 流 容 量			極數 P	定 價
		110V	220V	AF	AT	mA		
住宅分電盤用【LB】	LB30	2.5	2.5	30	30	30	2	360
	LB40			40	40			380

## 台芝漏電斷路器(漏電兼過負荷，短路保護專用型)

類別	型式	啓斷容量 KA 非對稱值/對稱值		電 流 容 量			極數 P	定 價
		220-240V	380-440V	AF	AT	mA		
配線用經濟型【LE】	LEN100	16/15	10	100	15,20,30,40,50	30,100	3	2,150
					60,75,100			2,350