


# 35W Single Output Switching Power Supply



- AC input range selectable by switch
- Protections: Short circuit / Over load
- Cooling by free air convection
- 100% full load burn-in test
- Low cost, high reliability
- 1 year warranty

AC input voltage range	85~132VAC/ 170~264VAC selectable by switch
AC inrush current	Cold start, 18A at 115VAC, 36A at 230VAC
DC adjustment range	±10% rated output voltage
Over load protection	105%~150% fold back current limiting, auto-recovery
Setup, rise, hold up time	200ms, 100ms, 30ms at full load and 230VAC
Withstand voltage	I/P-O/P:1.5KVAC, I/P-FG:1.5KVAC, 1minute
Working temperature	-10~60°C (refer to output derating curve)
Safety standards	Design refer to UL1012
EMC standards	Design refer to FCC part 15 J
Connection	5P / 9.5mm pitch terminal block
Packing	0.41kg; 30pcs / 13.4kg / 0.86CUFT

Stock No.	Model No.	Output	Tol.	R&N	Effi.
10021	S-35-5	5V, 0~7.0A	±2%	75mV	70%
10022	S-35-12	12V, 0~3.0A	±1%	100mV	76%
10023	S-35-15	15V, 0~2.4A	±1%	100mV	78%
10024	S-35-24	24V, 0~1.5A	±1%	100mV	78%